BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images, please do not report the images to the Image Problem Mailbox.

WHAT IS CLAIMED IS:

1. A method of reusing a photographic processing waste solution, comprising:

preparing a solidified matter from the photographic processing waste solution by a dry-solidification according to a thin film concentration method without removing ingredients accumulated during a photographic processing;

forming the solidified matter into granules; and

reusing the granules as a solid photographic processing agent.

2. The method as described in claim 1, which further comprises gathering waste solutions discharged in individual steps of photographic processing; and mixing the gathered waste solutions without removing ingredients accumulated in the individual steps.

3. The method as described in claim 1, which further comprises adding a chemical consumed during the photographic processing.

4. The method as described in claim 1, wherein the photographic processing waste solution is a waste solution

generated by a color paper processing.

5. The method as described in claim 1, wherein the solidified matter is prepared from the photographic processing waste solution by a dry-solidification according to a thin film concentration method at a temperature of 80°C or below.

6. The method as described in claim 1, wherein the solidified matter is prepared from the photographic processing waste solution by a dry-solidification according to a thin film concentration method at a temperature of 80°C or below under a reduced pressure.

7. The method as described in claim 1, wherein the solidified matter is prepared from the photographic processing waste solution by a dry-solidification according to a thin film concentration method without removing at least silver accumulated during the photographic processing.

8. The method as described in claim 1, wherein a reuse rate is from 70% to 90%, in which the reuse rate means a rate by weight of the amount of the solid matter obtained from the photographic waste solutions and reused

as a replenishing agent to the total amount by weight of the solid matter obtained from the photographic waste solutions.

9. The method as described in claim 1, which further comprises: recovering water vapor produced at the time of the dry-solidification of the photographic waste solutions; and liquefying the water vapor to utilize the water as the water for diluting the bleach-fix processing solution or the water of the rinsing bath.

10. The method as described in claim 1, wherein the photographic processing waste solution is a mixture of processing waste solutions discharged in a development-processing step, a bleach-fix processing step and at least one of a rinse and stabilization-processing step.

11. A solid photographic replenishing agent produced in accordance with the method as described in claim 1.